

VERTICAL & HORIZONTAL SCISSOR LIFTS | 800-4000 KG

Tables for high lifts and long goods. Table should be fixed into floor with bolted joints. Lifting height up to 4210 mm. Maintenance free pivot bushings. Large safety clearance between the scissors to avoid injuries. Lift cylinder with internal drainage. Safety valve to ensure safety in case of a hose burst. Low-noise power pack with built-in overload valve. Safety switch in top position. Moveable limit switch for adjusting full raised stop. 4 end-stops, incl. 4 loops which can be used e.g. when lifting total lift table into a pit. Low-noise power pack with built in overload valve. Cable for 3-phase connection 380V/16 Ah. Approves to EN1570-1.



MJ-Q801



HD1000



LV4000

| TECHNICAL INFORMATION | | | | | | | |
|--------------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------------|---------------------------|
| Art.no | HD1000 | HD2000 | HD4000 | HT1000 | MJ-Q801 | LV2000 | LV4000 |
| Type | Double scissor | Double scissor | Double scissor | Triple scissor | Four scissor | Horizontal double scissor | Horizontal double scissor |
| Capacity (kg) | 1000 | 2000 | 4000 | 1000 | 800 | 2000 | 4000 |
| Table area (LxW) (mm) | 1300x820 | 1300x850 | 1700x1200 | 1700x1000 | 1700x1000 | 2500x820 | 2500x850 |
| Base frame size (LxW) (mm) | 1250x680 | 1255x785 | 1600x930 | 1660x1000 | 1606x1010 | 2470x680 | 2470x785 |
| Stroke Length (mm) | 1475 | 1420 | 1650 | 2530 | 787 | 795 | 770 |
| Weight (kg) | 210 | 295 | 520 | 450 | 858 | 265 | 360 |
| Lifting height, min-max (mm) | 305-1780 | 360-1780 | 400-2050 | 470-3000 | 706-4210 | 205-1000 | 230-1000 |
| Lifting time to max height (s) | 20-25 | 25-30 | 30-35 | 45-50 | 60-65 | 15-20 | 25-30 |
| Lifting motor | 380V/50HZ 1,5 kW | 380V/50HZ 2,2 kW | 380V/50HZ 2,2 kW | 380V/50HZ 2,2 kW | 380V/50HZ 2,2 kW | 380V/50HZ 2,2 kW | 380V/50HZ 2,2 kW |
| Price | | | | | | | |